



## Bay Area AQMD Regulation 8 Rule 45

VOC Less Water Less Exempt Limits for version amended 12/3/08



Coating Category	Effective 10/1/09		Effective 1/1/10		
	lbs/gal (g/L)	lbs/gal (g/L)	lbs/gal (g/L)		
Solvent (Surface Cleaner)	.21 (25)*	.21 (25)*			
Pretreatments Coating	5.5 (660)	5.5 (660)			
Primer	2.1 (250)	2.1 (250)			
Primer Sealer	2.8 (340)	2.1 (340)			
Single-Stage Coating	3.5 (420)	2.8 (340)			
Color Coating	3.5 (420)	3.5 (420)			
Clear Coating	2.1 (250)	2.1 (250)			
Uniform Finish Coating	4.5 (540)	4.5 (540)			
Adhesion Promoter	7.0 (840)	4.5 (540)		* VOC content applies to this category only	
<b>Product Code &amp; Name</b>		<b>Reducer</b>	<b>Mix Ratio</b>	<b>VOC content</b>	
<b>Solvent (Substrate Cleaner)</b>				Limit: <b>0.21 lbs/gal (25 g/L)</b>	
SWX350 H2O-So-Clean Wax & Grease Remover		-	-	0.17 (20)	
SWX360 Waterborne Pre-Cleaner		water	1 : 2	0.20 (24)	
<b>Product Code &amp; Name</b>	<b>Hardener/Activator</b>	<b>Reducer</b>	<b>Mix Ratio</b>	<b>Applied VOC Less Water Less Exempt</b>	
<b>Pretreatment Coating</b>				Limit: <b>5.5 lbs/gal (660 g/L)</b>	
F3946 5.5 Wash Primer	F3947	-	1 : 1	5.48 (657)	
SXA1031 Etch Primer – Gray	-	-	Aerosol	N/A	
<b>Product Code &amp; Name</b>	<b>Hardener/Activator</b>	<b>Additives</b>	<b>Reducer</b>	<b>Mix Ratio</b>	<b>Applied VOC Less Water Less Exempt</b>
<b>Primer</b>					Limit: <b>2.1 lbs/gal (250 g/L)</b>
ESU410 2.1/2.8 Polyurethane Primer	ESU419	ESX590	-	5 : 1 + 6 oz / RTS gal	1.99 (238)
ESU470 2.1 VOC Wet on Wet Epoxy Primer - Gray	ESU479	-	ESR300 or ESR310	2 : 1 : 1 or 2 : 1 : 2 (reducer last)	2.07 (248)
F3970 Ultra High Solids Primer	F3971	F3400 or F3405	F3385, F3390 or F3395	3 : 1 + 6 oz / RTS gal + 10% optional reducer	2.07 (248)
F3998 2.1 VOC Primer Surfacer	F3999	-	-	2 : 1	1.99 (238)
<b>Single-Stage Coating</b>					Limit: <b>2.84 lbs/gal (340 g/L)</b>
ESSS Single Stage Polyurethane Enamel	ESH200	ESX500, ESX510, ESX520, ESX530 or ESX540	-	6 : 1 : 1	2.76 (331)
FDGU Single Stage Ultra high Solids Polyurethane Enamel	F3260	F3400, F3405 or F3410	F3385, F3390 or F3395	3 : 1 + 6 oz /RTS gal + 10% reducer	2.82 (338)
FDSU Ultra HS Polyurethane Single Stage	F3260	F3400, F3405 or F3410	F3385, F3390 or F3395	3 : 1 + 6 oz /RTS gal + 10% reducer	2.82 (338)
<b>Color Coating</b>					Limit: <b>3.5 lbs/gal (420 g/L)</b>
ESSS Polyurethane Basecoat	ESH210	ESB800	-	2 : 1 : 1	3.08 (369)
FBCH High Solids Polyurethane Basecoat	F3200 or F3260	F3440, F3441 or F3442	-	3 : 1 : 1	3.47 (416)
FBCS High Solids Basecoat - Fast	F3200 or F3260-	-	F3385	3 : 1 + 10%	3.04 (364)
FBCS High Solids Basecoat - Fast	F3200 or F3260-	-	F3330, F3340, F3350 or F3360	3 : 1 + 10%	3.41 (409)



## Bay Area AQMD Regulation 8 Rule 45

VOC Less Water Less Exempt Limits for version amended 12/3/08



Product Code & Name	Hardener/ Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
<b>Clear Coating</b>					<b>Limit: 2.1 lbs/gal (250 g/L)</b>
ESC621 2.1 VOC Clearcoat	ESH200	-	ESX711, ESX721, ESR300 or ESR310	4 : 1 : 1	2.06 (247)
F3921 2.1 VOC Clearcoat	F3210 or F3211	-	F3385, F3390 or F3395	3 : 1 : 1/2	2.05 (246)
<b>Additional Products: (listing not intended to be all inclusive)</b>					
FBCH500 FBCH Blending Clear	SUA4903 Advanced Plastic Bond				
FDGU500 FDGU Blending Clear	SXA840 OneChoice Blending Solvent				
SLV73 Fisheye Eliminator					
SU4901 Clean and Scuff Sponge					

This "Bay Area AQMD Rule 8-45 (PPG Delfleet)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Bay Area AQMD Rule 8-45 (PPG Delfleet)" wall chart does not include all currently compliant Delfleet products. The representative products listed are compliant with Rule 8-45 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 8-45 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.