

Bay Area AQMD



Regulation 8 Rule 45
VOC Less Water Less Exempt Limits for version amended 12/3/08

| | Effective 10/1/09 | | Effective 1/ | 1/10 | | |
|--|------------------------|--|------------------------------|---|---|--|
| | | s/gal (g/L) | lbs/gal (g/l | L) | | |
| Solvent (Surface Cleaner) | | 21 (25)* | .21 (25)* | | | |
| Pretreatments Coating | 5.5 (660) | | 5.5 (660) | | | |
| Primer | 2.1 (250) | | 2.1 (250) | | | |
| Primer Sealer | 2.8 (340) | | 2.1 (340) | | | |
| Single-Stage Coating | 3.5 (420) | | 2.8 (340) | | | |
| Color Coating | 3.5 (420) | | 3.5 (420) | | | |
| Clear Coating | 2.1 (250) | | 2.1 (250) | | | |
| Uniform Finish Coating | 4.5 (540) | | 4.5 (540) | | | |
| Adhesion Promoter | 7 | 7.0 (840) | 4.5 (540) | * VOC content app | * VOC content applies to this category only | |
| Product Code & Name | | | Reducei | r Mix Ratio | VOC content | |
| Solvent (Substrate Cleaner) | | | Limit: | 0.21 lbs/gal (2 | 5 g/L) | |
| SWX350 H2O-So-Clean Wax & Greas | | - | - | 0.17 (20) | | |
| SWX360 Waterborne Pre-Cleaner | | | water | 1:2 | 0.20 (24) | |
| Product Code & Name | | Hardener/ Activator | Reducer | Mix Ratio | Applied VOC Less Water Less Exempt | |
| Pretreatment Coating | | | Limit: | 5.5 lbs/gal | | |
| F3946 5.5 Wash Primer | | F3947 | - | 1:1 | 5.48 (657) | |
| SXA1031 Etch Primer – Gray | | - | - | Aerosol | N/A | |
| Product Code & Name | Hardener/ Activator | Additives | Reducer | Mix Ratio | Applied VOC Less Water Less Exempt | |
| Primer | | | Limit: | 2.1 lbs/gal (2 | 250 g/L) | |
| ESU410 2.1/2.8 Polyurethane Primer | ESU419 | ESX590 | - | 5:1+6oz/RTSgal | 1.99 (238) | |
| ESU470 2.1 VOC Wet on Wet Epoxy Primer - Gray | ESU479 | - | ESR300 or ESR310 | 2:1:1 or 2:1:2 (reducer last) | 2.07 (248) | |
| F3970 Ultra High Solids Primer | F3971 | F3400 or F3405 | F3385, F3390 or F3395 | 3:1 + 6 oz / RTS gal + 10% optional reducer | 2.07 (248) | |
| F3998 2.1 VOC Primer Surfacer | F3999 | - | - | 2:1 | 1.99 (238) | |
| Single-Stage Coating | | | Limit: | 2.84 lbs/gal (| 340 g/L) | |
| ESSS Single Stage Polyurethane Enamel | ESH200 | ESX500, ESX510, ESX520, ESX530 or ESX540 | - | 6 : 1 :1 | 2.76 (331) | |
| FDGU Single Stage Ultra high Solids Polyurethane Enamel | F3260 | F3400, F3405 or F3410 | F3385, F3390 or F3395 | 3:1+6 oz /RTS gal + 10% reducer | 2.82 (338) | |
| FDSU Ultra HS Polyurethane Single Stage | F3260 | F3400, F3405 or F3410 | F3385, F3390 or F3395 | 3:1+6 oz /RTS gal + 10% reducer | 2.82 (338) | |
| Color Coating | | | Limit: | 3.5 lbs/gal (4 | 420 g/L) | |
| FBCH High Solids Polyurethane Basecoat | F3200 or F3260 | F3440, F3441 or F3442 | - | 3:1:1 | 3.47 (416) | |
| FBCS High Solids Basecoat - Fast | F3200 or F3260- | - | F3385 | 3:1+10% | 3.04 (364) | |
| FBCS High Solids Basecoat - Fast | F3200 or F3260- | - | F3330, F3340, F3350 or | 3:1+10% | 3.41 (409) | |

© 2009 PPG Industries VOC 45 DEL,10/09

F3360



Bay Area AQMD

Regulation 8 Rule 45



VOC Less Water Less Exempt Limits for version amended 12/3/08

| Product Code & Name | Hardener/ Activator | Additives | Reducer | Mix Ratio | Applied VOC Less Water Less Exempt |
|--|------------------------|--|-----------------------------|-------------|------------------------------------|
| Clear Coating | | | Limit: | 2.1 lbs/gal | (250 g/L) |
| F3921 2.1 VOC Clearcoat | F3210 or F3211 | - - | F3385, F3390 or F3395 | 3:1:1/2 | 2.05 (246) |
| Additional Products: (listing not intend | ded to be all inclus | ive) | | | |
| FDGH500 FDGH Blending Clear FDGU500 FDGU Blending Clear FDSH500 FDSH Blending Clear SLV73 Fisheye Eliminator SU4901 Clean and Scuff Sponge | | Advanced Plastic B OneChoice Blending | | | |
| | | | | | |

This "Bay Area AQMD Rule 8-45 (PPG Delfleet)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Bay Area AQMD Rule 8-45 (PPG Deltfleet)" wall chart does not include all currently compliant Delfleet products. The representative products listed are compliant with Rule 8-45 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 8-45 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

© 2009 PPG Industries VOC 45 DEL,10/09