

Bug and Tar Remover

SX1009

2.9 VOC Bug and Tar Remover

SX1009 2.9 VOC Bug and Tar Remover is specifically designed to remove bugs, road tar, wax, grease, silicone, engine oil and other contaminants. It can also be used on bare metal, plastics, primers, or cured automotive finishes. SX 1009 is packaged ready-to-use.

It is compliant in many markets with a VOC of 2.9 lbs per gallon.



Features

- Ready to Use

Advantages

- Convenient
- Low VOC

Benefits

- Simple to Use
- Reduced Emissions

Required Products

- SX1009 2.9 VOC Bug and Tar Remover

Compatible Products

- SX1009 2.9 VOC Bug and Tar Remover is for use with PPG and Nexa Brand refinish products.

Compatible Products

- OEM Surfaces
- Cured and Dried Automotive Surfaces
- Ferrous and non-ferrous metals
- Automotive Plastics

Preparation of Substrate:



- Wash surface with soap and water before cleaning.
- Clean surface before and after sanding.
- Apply a generous amount of SX1009 to a PPG clean white disposable cloth or apply with a hand held spray bottle.



- Initial application floats contaminants to the surface where the second wipe with a clean, dry white cloth will remove the contaminants.
- For best results, wiping dry with clean white cloth in one direction while the surface is still wet will aid in eliminating instead of smearing of the contaminants.



- Tack the entire surface prior to being painted with a SX1070 tack rag.
- Note: Test surface for sensitive substrates.

2.9 VOC Bug and Tar Remover

SX1009

Technical Data:

Color:	Clear
Intended Use:	Solvent (Substrate Cleaner)
VOC Content	2.89 lbs/gal (346 g/L)
Wt.% VOC	31.8%
Density:	9.07
Flashpoint (PMCC):	93°F

Important:

Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515. IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.

PPG Industries

World Leaders in Automotive Finishes

PPG Industries
19699 Progress Drive
Strongsville, OH 44149
1-800-647-6050

PPG Canada Inc.
2301 Royal Windsor Drive, Unit #6
Mississauga, Ontario, Canada L5J 1K5
1-888-310-4762